


V_R	1700V
I_F	25A ^{*1}
Q_C	69nC

●Features

- 1) Shorter recovery time
- 2) Reduced temperature dependence
- 3) High-speed switching possible

●Inner Circuit



●Construction

Silicon carbide epitaxial planar type
Schottky diode

●Absolute Maximum Ratings ($T_j = 25^\circ\text{C}$)

Parameter	Symbol	Value	Unit
Reverse voltage (repetitive peak)	V_{RM}	1700	V
Reverse voltage (DC)	V_R	1700	V
Continuous forward current ($T_c=145^\circ\text{C}$)	I_F	25 ^{*1}	A
Surge non-repetitive forward current	I_{FSM} ^{*2}	PW=10ms sinusoidal, $T_j=25^\circ\text{C}$	90 A
		PW=10ms sinusoidal, $T_j=150^\circ\text{C}$	68 A
		PW=10μs square, $T_j=25^\circ\text{C}$	360 A
i^2t value	$\int i^2 dt$ ^{*2}	$1 \leq PW \leq 10\text{ms}$, $T_j=25^\circ\text{C}$	41 A^2s
		$1 \leq PW \leq 10\text{ms}$, $T_j=150^\circ\text{C}$	23 A^2s
Junction temperature	T_j	175	$^\circ\text{C}$
Range of storage temperature	T_{stg}	-55 to +175	$^\circ\text{C}$

*1 Limited by T_j *2 Assumes $Z_{th(j-a)}$ of 0.28 $^\circ\text{C}/\text{W}$ or less. (Pulse Width = 8.3ms)

●Electrical characteristics ($T_j = 25^\circ\text{C}$)

Parameter	Symbol	Conditions	Values			Unit
			Min.	Typ.	Max.	
DC blocking voltage	V_{DC}	$I_R=0.15\text{mA}$	1700	-	-	V
Forward voltage	V_F	$I_F=25\text{A}, T_j=25^\circ\text{C}$	-	1.65	1.95	V
		$I_F=25\text{A}, T_j=150^\circ\text{C}$	-	2.5	-	V
		$I_F=25\text{A}, T_j=175^\circ\text{C}$	-	2.8	-	V
Reverse current	I_R	$V_R=1700\text{V}, T_j=25^\circ\text{C}$	-	2.5	150	μA
		$V_R=1700\text{V}, T_j=150^\circ\text{C}$	-	55	-	μA
		$V_R=1700\text{V}, T_j=175^\circ\text{C}$	-	125	-	μA
Total capacitance	C	$V_R=1\text{V}, f=1\text{MHz}$	-	1560	-	pF
		$V_R=1700\text{V}, f=1\text{MHz}$	-	85	-	pF
Total capacitive charge	Q_C	$V_R=800\text{V}, di/dt=500\text{A}/\mu\text{s}$	-	69	-	nC
Switching time	t_C	$V_R=800\text{V}, di/dt=500\text{A}/\mu\text{s}$	-	23	-	ns

●Electrical characteristic curves

Fig.1 $V_F - I_F$ Characteristics




Fig.2 $V_F - I_F$ Characteristics




Fig.3 $V_R - I_R$ Characteristics






Fig.4 $V_R - C_t$ Characteristics



●Electrical characteristic curves

Fig.5 Surge non-repetitive forward current vs. Pulse width (Sinusoidal waveform)*



* Assumes $Z_{th(j-a)}$ of 0.38 °C/W or less.
(Pulse Width = 8.3ms)

Fig.6 Typical capacitance store energy





Fig.7 Equivalent forward current curve



$$V_F = V_{th} + R_{diff} I_F$$

$$V_{th} (T_j) = a_0 + a_1 T_j$$

$$R_{diff} (T_j) = b_0 + b_1 T_j + b_2 T_j^2$$

Symbol	Typical Value	Unit
a_0	9.21E-01	V
a_1	-1.52E-03	V/°C
b_0	2.40E-02	Ω
b_1	1.62E-04	Ω/°C
b_2	1.12E-06	Ω/°C ²

T_j in °C; -55 °C < T_j < °C ; I_F < 50A

Notes

- 1) The information contained herein is subject to change without notice.
- 2) Before you use our Products, please contact our sales representative and verify the latest specifications.
- 3) Although ROHM is continuously working to improve product reliability and quality, semiconductors can break down and malfunction due to various factors. Therefore, in order to prevent personal injury or fire arising from failure, please take safety measures such as complying with the derating characteristics, implementing redundant and fire prevention designs, and utilizing backups and fail-safe procedures. ROHM shall have no responsibility for any damages arising out of the use of our Products beyond the rating specified by ROHM.
- 4) Examples of application circuits, circuit constants and any other information contained herein are provided only to illustrate the standard usage and operations of the Products. The peripheral conditions must be taken into account when designing circuits for mass production.
- 5) The technical information specified herein is intended only to show the typical functions of and examples of application circuits for the Products. ROHM does not grant you, explicitly or implicitly, any license to use or exercise intellectual property or other rights held by ROHM or any other parties. ROHM shall have no responsibility whatsoever for any dispute arising out of the use of such technical information.
- 6) The Products specified in this document are not designed to be radiation tolerant.
- 7) For use of our Products in applications requiring a high degree of reliability (as exemplified below), please contact and consult with a ROHM representative : transportation equipment (i.e. cars, ships, trains), primary communication equipment, traffic lights, fire/crime prevention, safety equipment, medical systems, and power transmission systems.
- 8) Do not use our Products in applications requiring extremely high reliability, such as aerospace equipment, nuclear power control systems, and submarine repeaters.
- 9) ROHM shall have no responsibility for any damages or injury arising from non-compliance with the recommended usage conditions and specifications contained herein.
- 10) ROHM has used reasonable care to ensure the accuracy of the information contained in this document. However, ROHM does not warrants that such information is error-free, and ROHM shall have no responsibility for any damages arising from any inaccuracy or misprint of such information.
- 11) Please use the Products in accordance with any applicable environmental laws and regulations, such as the RoHS Directive. For more details, including RoHS compatibility, please contact a ROHM sales office. ROHM shall have no responsibility for any damages or losses resulting non-compliance with any applicable laws or regulations.
- 12) When providing our Products and technologies contained in this document to other countries, you must abide by the procedures and provisions stipulated in all applicable export laws and regulations, including without limitation the US Export Administration Regulations and the Foreign Exchange and Foreign Trade Act.
- 13) This document, in part or in whole, may not be reprinted or reproduced without prior consent of ROHM.



Thank you for your accessing to ROHM product informations.
More detail product informations and catalogs are available, please contact us.

ROHM Customer Support System

<http://www.rohm.com/contact/>