

## 3-V TO 5.5-V MULTICHANNEL RS-232 LINE DRIVER/RECEIVER WITH $\pm 15$ -kV ESD PROTECTION

Check for Samples: [MAX3222E](#)

### FEATURES

- **ESD Protection for RS-232 Bus Pins**
  - $\pm 15$ -kV Human-Body Model (HBM)
  - $\pm 8$ -kV IEC61000-4-2, Contact Discharge
  - $\pm 15$ -kV IEC61000-4-2, Air-Gap Discharge
- **Meets or Exceeds the Requirements of TIA/EIA-232-F and ITU v.28 Standards**
- **Operates With 3-V to 5.5-V  $V_{CC}$  Supply**
- **Operates up to 500 kbit/s**
- **Two Drivers and Two Receivers**
- **Low Standby Current . . . 1  $\mu$ A Typ**
- **External Capacitors . . . 4  $\times$  0.1  $\mu$ F**
- **Accepts 5-V Logic Input With 3.3-V Supply**
- **Alternative High-Speed Pin-Compatible Device (1 Mbit/s) for SNx5C3222E**

### APPLICATIONS

- **Battery-Powered Systems**
- **PDA's**
- **Notebooks**
- **Laptops**
- **Palmtop PCs**
- **Hand-Held Equipment**


### DESCRIPTION/ORDERING INFORMATION

The MAX3222E consists of two line drivers, two line receivers, and a dual charge-pump circuit with  $\pm 15$ -kV ESD protection pin to pin (serial-port connection pins, including GND).

The MAX3222E can be placed in the power-down mode by setting the power-down ( $\overline{\text{PWRDOWN}}$ ) input low, which draws only 1  $\mu$ A from the power supply. When the device is powered down, the receivers remain active while the drivers are placed in the high-impedance state. Also, during power down, the onboard charge pump is disabled;  $V+$  is lowered to  $V_{CC}$ , and  $V-$  is raised toward GND. Receiver outputs also can be placed in the high-impedance state by setting enable ( $\overline{\text{EN}}$ ) high.

The device meets the requirements of TIA/EIA-232-F and provides the electrical interface between an asynchronous communication controller and the serial-port connector. The charge pump and four small external capacitors allow operation from a single 3-V to 5.5-V supply. The device operates at typical data signaling rates up to 500 kbit/s and a maximum of 30-V/ $\mu$ s driver output slew rate.

DB, DW, OR PW PACKAGE  
(TOP VIEW)



NC – No internal connection



Please be aware that an important notice concerning availability, standard warranty, and use in critical applications of Texas Instruments semiconductor products and disclaimers thereto appears at the end of this data sheet.

**ORDERING INFORMATION**

| T <sub>A</sub> | PACKAGE <sup>(1)</sup> <sup>(2)</sup> |              | ORDERABLE PART NUMBER | TOP-SIDE MARKING |
|----------------|---------------------------------------|--------------|-----------------------|------------------|
| 0°C to 70°C    | SOIC – DW                             | Tube of 25   | MAX3222ECDW           | MAX3222EC        |
|                |                                       | Reel of 2000 | MAX3222ECDWR          |                  |
|                | SSOP – DB                             | Tube of 70   | MAX3222ECDB           | MP222EC          |
|                |                                       | Reel of 2000 | MAX3222ECDBR          |                  |
|                | TSSOP – PW                            | Tube of 70   | MAX3222ECPW           | MP222EC          |
|                |                                       | Reel of 2000 | MAX3222ECPWR          |                  |
| –40°C to 85°C  | SOIC – DW                             | Tube of 25   | MAX3222EIDW           | MAX3222EI        |
|                |                                       | Reel of 2000 | MAX3222EIDWR          |                  |
|                | SSOP – DB                             | Tube of 70   | MAX3222EIDB           | MP222EI          |
|                |                                       | Reel of 2000 | MAX3222EIDBR          |                  |
|                | TSSOP – PW                            | Tube of 70   | MAX3222EIPW           | MP222EI          |
|                |                                       | Reel of 2000 | MAX3222EIPWR          |                  |

(1) Package drawings, thermal data, and symbolization are available at [www.ti.com/packaging](http://www.ti.com/packaging).

(2) For the most current package and ordering information, see the Package Option Addendum at the end of this document, or see the TI website at [www.ti.com](http://www.ti.com).

**Table 1. FUNCTION TABLES****EACH DRIVER <sup>(1)</sup>**

| INPUTS |         | OUTPUT<br>DOUT |
|--------|---------|----------------|
| DIN    | PWRDOWN |                |
| X      | L       | Z              |
| L      | H       | H              |
| H      | H       | L              |


(1) H = high level, L = low level, X = irrelevant, Z = high impedance

**Table 2. EACH RECEIVER <sup>(1)</sup>**

| INPUTS |    | OUTPUT<br>ROUT |
|--------|----|----------------|
| RIN    | EN |                |
| L      | L  | H              |
| H      | L  | L              |
| X      | H  | Z              |
| Open   | L  | H              |

(1) H = high level, L = low level, X = irrelevant,  
Z = high impedance (off),  
Open = input disconnected or connected driver off

### LOGIC DIAGRAM (POSITIVE LOGIC)



Pin numbers are for the DB, DW, and PW packages.

### ABSOLUTE MAXIMUM RATINGS<sup>(1)</sup>

over operating free-air temperature range (unless otherwise noted)

|                  |   |   | MIN   | MAX                   | UNIT |
|------------------|---|---|-------|-----------------------|------|
| V <sub>CC</sub>  | Supply voltage range <sup>(2)</sup>                     |   | −0.3  | 6                     | V    |
| V+               | Positive-output supply voltage range <sup>(2)</sup>     |   | −0.3  | 7                     | V    |
| V−               | Negative-output supply voltage range <sup>(2)</sup>     |   | 0.3   | −7                    | V    |
| V+ − V−          | Supply voltage difference <sup>(2)</sup>                |   |       | 13                    | V    |
| V <sub>I</sub>   | Input voltage range                                     | Driver ( $\overline{\text{EN}}$ , $\overline{\text{PWRDOWN}}$ ) | −0.3  | 6                     | V    |
|                  |   | Receiver  | −25   | 25                    |      |
| V <sub>O</sub>   | Output voltage range                                    | Driver  | −13.2 | 13.2                  | V    |
|                  |   | Receiver  | −0.3  | V <sub>CC</sub> + 0.3 |      |
| θ <sub>JA</sub>  | Package thermal impedance <sup>(3)</sup> <sup>(4)</sup> | DB package  |       | 70                    | °C/W |
|                  |   | DW package  |       | 58                    |      |
|                  |   | PW package  |       | 83                    |      |
| T <sub>J</sub>   | Operating virtual junction temperature                  |   |       | 150                   | °C   |
| T <sub>stg</sub> | Storage temperature range                               |   | −65   | 150                   | °C   |

- (1) Stresses beyond those listed under "absolute maximum ratings" may cause permanent damage to the device. These are stress ratings only, and functional operation of the device at these or any other conditions beyond those indicated under "recommended operating conditions" is not implied. Exposure to absolute-maximum-rated conditions for extended periods may affect device reliability.
- (2) All voltages are with respect to network GND.
- (3) Maximum power dissipation is a function of T<sub>J</sub>(max),  $\theta_{JA}$ , and T<sub>A</sub>. The maximum allowable power dissipation at any allowable ambient temperature is P<sub>D</sub> = (T<sub>J</sub>(max) – T<sub>A</sub>)/ $\theta_{JA}$ . Operating at the absolute maximum T<sub>J</sub> of 150°C can affect reliability.
- (4) The package thermal impedance is calculated in accordance with JESD 51-7.

**RECOMMENDED OPERATING CONDITIONS<sup>(1)</sup>**See [Figure 5](#)

|                 |   |   |                         | MIN | NOM | MAX | UNIT |    |
|-----------------|---|---|-------------------------|-----|-----|-----|------|----|
| Supply voltage  |   |   | V <sub>CC</sub> = 3.3 V | 3   | 3.3 | 3.6 | V    |    |
|                 |   |   | V <sub>CC</sub> = 5 V   | 4.5 | 5   | 5.5 |      |    |
| V <sub>IH</sub> | Driver and control high-level input voltage | DIN, $\overline{EN}$ , $\overline{PWRDOWN}$ | V <sub>CC</sub> = 3.3 V | 2   |     |     | V    |    |
|                 |   |   | V <sub>CC</sub> = 5 V   | 2.4 |     |     |      |    |
| V <sub>IL</sub> | Driver and control low-level input voltage  | DIN, $\overline{EN}$ , $\overline{PWRDOWN}$ |                         | 0.8 |     |     | V    |    |
| V <sub>I</sub>  | Driver and control input voltage            | DIN, $\overline{EN}$ , $\overline{PWRDOWN}$ |                         | 0   |     |     | 5.5  | V  |
| V <sub>I</sub>  | Receiver input voltage                      |   |                         | −25 |     |     | 25   | V  |
| T <sub>A</sub>  | Operating free-air temperature              |   | MAX3222EC               | 0   |     |     | 70   | °C |
|                 |   |   | MAX3222EI               | −40 |     |     | 85   |    |

(1) Test conditions are C1–C4 = 0.1  $\mu\text{F}$  at  $V_{CC} = 3.3\text{ V} \pm 0.3\text{ V}$ ; C1 = 0.047  $\mu\text{F}$ , C2–C4 = 0.33  $\mu\text{F}$  at  $V_{CC} = 5\text{ V} \pm 0.5\text{ V}$ .

**ELECTRICAL CHARACTERISTICS<sup>(1)</sup>**over recommended ranges of supply voltage and operating free-air temperature (unless otherwise noted) (see [Figure 5](#))

| PARAMETER |  | TEST CONDITIONS                           | MIN        | TYP <sup>(2)</sup> | MAX     | UNIT          |
|-----------|--|---|------------|--------------------|---------|---------------|
| $I_I$     | Input leakage current ( $\overline{EN}$ , $\overline{PWRDOWN}$ ) |   | $\pm 0.01$ |                    | $\pm 1$ | $\mu\text{A}$ |
| $I_{CC}$  | Supply current   | No load, $\overline{PWRDOWN}$ at $V_{CC}$ | 0.3        |                    | 1       | mA            |
|           | Supply current (powered off)                                     | No load, $\overline{PWRDOWN}$ at GND      | 1          |                    | 10      | $\mu\text{A}$ |

(1) Test conditions are C1–C4 = 0.1  $\mu\text{F}$  at  $V_{CC} = 3.3\text{ V} \pm 0.3\text{ V}$ ; C1 = 0.047  $\mu\text{F}$ , C2–C4 = 0.33  $\mu\text{F}$  at  $V_{CC} = 5\text{ V} \pm 0.5\text{ V}$ .

(2) All typical values are at  $V_{CC} = 3.3\text{ V}$  or  $V_{CC} = 5\text{ V}$ , and  $T_A = 25^\circ\text{C}$ .

## DRIVER SECTION

### Electrical Characteristics<sup>(1)</sup>

over recommended ranges of supply voltage and operating free-air temperature (unless otherwise noted) (see [Figure 5](#))

| PARAMETER   | TEST CONDITIONS   | MIN | TYP <sup>(2)</sup> | MAX        | UNIT |
|---|---|-----|--------------------|------------|------|
| V <sub>OH</sub> High-level output voltage                   | DOUT at R <sub>L</sub> = 3 kΩ to GND, DIN = GND   | 5   | 5.4                |            | V    |
| V <sub>OL</sub> Low-level output voltage                    | DOUT at R <sub>L</sub> = 3 kΩ to GND, DIN = V <sub>CC</sub>   | –5  | –5.4               |            | V    |
| I <sub>IH</sub> High-level input current                    | V <sub>I</sub> = V <sub>CC</sub>  |     | ±0.01              | ±1         | μA   |
| I <sub>IL</sub> Low-level input current                     | V <sub>I</sub> at GND   |     | ±0.01              | ±1         | μA   |
| I <sub>OS</sub> Short-circuit output current <sup>(3)</sup> | V <sub>CC</sub> = 3.6 V<br>V <sub>CC</sub> = 5.5 V  |     | ±35                | ±60        | mA   |
| r <sub>o</sub> Output resistance                            | V <sub>CC</sub> , V <sub>+</sub> , and V <sub>–</sub> = 0 V, V <sub>O</sub> = ±2 V  | 300 | 10M                |            | Ω    |
| I <sub>OZ</sub> Output leakage current                      | PWRDOWN = GND<br>V <sub>CC</sub> = 3 V to 3.6 V,<br>V <sub>O</sub> = ±12 V<br>V <sub>CC</sub> = 4.5 V to 5.5 V,<br>V <sub>O</sub> = ±10 V |     |                    | ±25<br>±25 | μA   |

(1) Test conditions are C1–C4 = 0.1 μF at V<sub>CC</sub> = 3.3 V ± 0.3 V; C1 = 0.047 μF, C2–C4 = 0.33 μF at V<sub>CC</sub> = 5 V ± 0.5 V.

(2) All typical values are at V<sub>CC</sub> = 3.3 V or V<sub>CC</sub> = 5 V, and T<sub>A</sub> = 25°C.

(3) Short-circuit durations should be controlled to prevent exceeding the device absolute power dissipation ratings, and not more than one output should be shorted at a time.

### Switching Characteristics<sup>(1)</sup>

over recommended ranges of supply voltage and operating free-air temperature (unless otherwise noted) (see [Figure 5](#))

| PARAMETER   | TEST CONDITIONS   | MIN    | TYP <sup>(2)</sup> | MAX      | UNIT   |
|---|---|--------|--------------------|----------|--------|
| Maximum data rate   | C <sub>L</sub> = 1000 pF,<br>One DOUT switching,<br>R <sub>L</sub> = 3 kΩ,<br>See <a href="#">Figure 1</a>                            | 250    | 500                |          | kbit/s |
| t <sub>sk(p)</sub> Pulse skew <sup>(3)</sup>                              | C <sub>L</sub> = 150 pF to 2500 pF,<br>See <a href="#">Figure 2</a><br>R <sub>L</sub> = 3 kΩ to 7 kΩ,                                 |        | 300                |          | ns     |
| SR(tr) Slew rate,<br>transition region<br>(see <a href="#">Figure 1</a> ) | R <sub>L</sub> = 3 kΩ to 7 kΩ,<br>V <sub>CC</sub> = 3.3 V<br>C <sub>L</sub> = 150 pF to 1000 pF<br>C <sub>L</sub> = 150 pF to 2500 pF | 6<br>4 |                    | 30<br>30 | V/μs   |

(1) Test conditions are C1–C4 = 0.1 μF at V<sub>CC</sub> = 3.3 V ± 0.3 V; C1 = 0.047 μF, C2–C4 = 0.33 μF at V<sub>CC</sub> = 5 V ± 0.5 V.

(2) All typical values are at V<sub>CC</sub> = 3.3 V or V<sub>CC</sub> = 5 V, and T<sub>A</sub> = 25°C.

(3) Pulse skew is defined as |t<sub>PLH</sub> – t<sub>PHL</sub>| of each channel of the same device.

### ESD Protection

|                        |                                 | TYP | UNIT |
|------------------------|---------------------------------|-----|------|
| Driver outputs (DOUTx) | Human-Body Model (HBM)          | ±15 | kV   |
|                        | IEC61000-4-2, Air-Gap Discharge | ±15 |      |
|                        | IEC61000-4-2, Contact Discharge | ±8  |      |

## RECEIVER SECTION

### Electrical Characteristics<sup>(1)</sup>

over recommended ranges of supply voltage and operating free-air temperature (unless otherwise noted) (see [Figure 5](#))

| PARAMETER        |   | TEST CONDITIONS                | MIN                   | TYP <sup>(2)</sup>    | MAX | UNIT |
|------------------|---|--------------------------------|-----------------------|-----------------------|-----|------|
| V <sub>OH</sub>  | High-level output voltage                               | I <sub>OH</sub> = –1 mA        | V <sub>CC</sub> – 0.6 | V <sub>CC</sub> – 0.1 |     | V    |
| V <sub>OL</sub>  | Low-level output voltage                                | I <sub>OL</sub> = 1.6 mA       |                       |                       | 0.4 | V    |
| V <sub>IT+</sub> | Positive-going input threshold voltage                  | V <sub>CC</sub> = 3.3 V        |                       | 1.5                   | 2.4 | V    |
|                  |   | V <sub>CC</sub> = 5 V          |                       | 1.8                   | 2.4 |      |
| V <sub>IT–</sub> | Negative-going input threshold voltage                  | V <sub>CC</sub> = 3.3 V        | 0.6                   | 1.2                   |     | V    |
|                  |   | V <sub>CC</sub> = 5 V          | 0.8                   | 1.5                   |     |      |
| V <sub>hys</sub> | Input hysteresis (V <sub>IT+</sub> – V <sub>IT–</sub> ) |                                |                       | 0.3                   |     | V    |
| I <sub>OZ</sub>  | Output leakage current                                  | $\overline{\text{EN}}$ = 1     |                       | ±0.05                 | ±10 | μA   |
| r <sub>i</sub>   | Input resistance  | V <sub>I</sub> = ±3 V to ±25 V | 3                     | 5                     | 7   | kΩ   |

(1) Test conditions are C1–C4 = 0.1 μF at V<sub>CC</sub> = 3.3 V ± 0.3 V; C1 = 0.047 μF, C2–C4 = 0.33 μF at V<sub>CC</sub> = 5 V ± 0.5 V.

(2) All typical values are at V<sub>CC</sub> = 3.3 V or V<sub>CC</sub> = 5 V, and T<sub>A</sub> = 25°C.

### Switching Characteristics<sup>(1)</sup>

over recommended ranges of supply voltage and operating free-air temperature (unless otherwise noted)

| PARAMETER          |   | TEST CONDITIONS  | TYP <sup>(2)</sup> | UNIT |
|--------------------|---|--|--------------------|------|
| t <sub>PLH</sub>   | Propagation delay time, low- to high-level output | C <sub>L</sub> = 150 pF, See <a href="#">Figure 3</a>                        | 300                | ns   |
| t <sub>PHL</sub>   | Propagation delay time, high- to low-level output | C <sub>L</sub> = 150 pF, See <a href="#">Figure 3</a>                        | 300                | ns   |
| t <sub>en</sub>    | Output enable time                                | C <sub>L</sub> = 150 pF, R <sub>L</sub> = 3 kΩ, See <a href="#">Figure 4</a> | 200                | ns   |
| t <sub>dis</sub>   | Output disable time                               | C <sub>L</sub> = 150 pF, R <sub>L</sub> = 3 kΩ, See <a href="#">Figure 4</a> | 200                | ns   |
| t <sub>sk(p)</sub> | Pulse skew <sup>(3)</sup>                         | See <a href="#">Figure 3</a>   | 300                | ns   |

(1) Test conditions are C1–C4 = 0.1 μF at V<sub>CC</sub> = 3.3 V ± 0.3 V; C1 = 0.047 μF, C2–C4 = 0.33 μF at V<sub>CC</sub> = 5 V ± 0.5 V.


(2) All typical values are at V<sub>CC</sub> = 3.3 V or V<sub>CC</sub> = 5 V, and T<sub>A</sub> = 25°C.

(3) Pulse skew is defined as |t<sub>PLH</sub> – t<sub>PHL</sub>| of each channel of the same device.

## ESD Protection


|                        |                                 | TYP | UNIT |
|------------------------|---------------------------------|-----|------|
| Receiver inputs (RINx) | Human-Body Model (HBM)          | ±15 | kV   |
|                        | IEC61000-4-2, Air-Gap Discharge | ±15 |      |
|                        | IEC61000-4-2, Contact Discharge | ±8  |      |

## PARAMETER MEASUREMENT INFORMATION




- A. C<sub>L</sub> includes probe and jig capacitance.
- B. The pulse generator has the following characteristics: PRR = 250 kbit/s, Z<sub>O</sub> = 50 Ω, 50% duty cycle, t<sub>r</sub> ≤ 10 ns, t<sub>f</sub> ≤ 10 ns.

Figure 1. Driver Slew Rate



- A. C<sub>L</sub> includes probe and jig capacitance.
- B. The pulse generator has the following characteristics: PRR = 250 kbit/s, Z<sub>O</sub> = 50 Ω, 50% duty cycle, t<sub>r</sub> ≤ 10 ns, t<sub>f</sub> ≤ 10 ns.



Figure 2. Driver Pulse Skew



- A. C<sub>L</sub> includes probe and jig capacitance.
- B. The pulse generator has the following characteristics: Z<sub>O</sub> = 50 Ω, 50% duty cycle, t<sub>r</sub> ≤ 10 ns, t<sub>f</sub> ≤ 10 ns.

Figure 3. Receiver Propagation Delay Times

## PARAMETER MEASUREMENT INFORMATION (continued)




- A.  $C_L$  includes probe and jig capacitance.
- B. The pulse generator has the following characteristics:  $Z_O = 50 \Omega$ , 50% duty cycle,  $t_r \leq 10 \text{ ns}$ ,  $t_f \leq 10 \text{ ns}$ .

**Figure 4. Receiver Enable and Disable Times**



## APPLICATION INFORMATION



† C3 can be connected to V<sub>CC</sub> or GND.

NOTES: A. Resistor values shown are nominal.

B. NC – No internal connection

C. Nonpolarized ceramic capacitors are acceptable. If polarized tantalum or electrolytic capacitors are used, they should be connected as shown.

**V<sub>CC</sub> vs CAPACITOR VALUES**

| V <sub>CC</sub> | C1       | C2, C3, and C4 |
|-----------------|----------|----------------|
| 3.3 V ± 0.3 V   | 0.1 μF   | 0.1 μF         |
| 5 V ± 0.5 V     | 0.047 μF | 0.33 μF        |
| 3 V to 5.5 V    | 0.1 μF   | 0.47 μF        |

**Figure 5. Typical Operating Circuit and Capacitor Values**

## PACKAGING INFORMATION

| Orderable Device | Status<br>(1) | Package Type | Package<br>Drawing | Pins | Package<br>Qty | Eco Plan<br>(2) | Lead finish/<br>Ball material<br>(6) | MSL Peak Temp<br>(3) | Op Temp (°C) | Device Marking<br>(4/5) | Samples                 |
|------------------|---------------|--------------|--------------------|------|----------------|-----------------|--------------------------------------|----------------------|--------------|-------------------------|-------------------------|
| MAX3222ECDB      | ACTIVE        | SSOP         | DB                 | 20   | 70             | RoHS & Green    | NIPDAU                               | Level-1-260C-UNLIM   | 0 to 70      | MP222EC                 | <a href="#">Samples</a> |
| MAX3222ECDBR     | ACTIVE        | SSOP         | DB                 | 20   | 2000           | RoHS & Green    | NIPDAU                               | Level-1-260C-UNLIM   | 0 to 70      | MP222EC                 | <a href="#">Samples</a> |
| MAX3222ECDW      | ACTIVE        | SOIC         | DW                 | 20   | 25             | RoHS & Green    | NIPDAU                               | Level-1-260C-UNLIM   | 0 to 70      | MAX3222EC               | <a href="#">Samples</a> |
| MAX3222ECDWR     | ACTIVE        | SOIC         | DW                 | 20   | 2000           | RoHS & Green    | NIPDAU                               | Level-1-260C-UNLIM   | 0 to 70      | MAX3222EC               | <a href="#">Samples</a> |
| MAX3222ECPW      | ACTIVE        | TSSOP        | PW                 | 20   | 70             | RoHS & Green    | NIPDAU                               | Level-1-260C-UNLIM   | 0 to 70      | MP222EC                 | <a href="#">Samples</a> |
| MAX3222ECPWG4    | ACTIVE        | TSSOP        | PW                 | 20   | 70             | RoHS & Green    | NIPDAU                               | Level-1-260C-UNLIM   | 0 to 70      | MP222EC                 | <a href="#">Samples</a> |
| MAX3222ECPWR     | ACTIVE        | TSSOP        | PW                 | 20   | 2000           | RoHS & Green    | NIPDAU                               | Level-1-260C-UNLIM   | 0 to 70      | MP222EC                 | <a href="#">Samples</a> |
| MAX3222EIDB      | ACTIVE        | SSOP         | DB                 | 20   | 70             | RoHS & Green    | NIPDAU                               | Level-1-260C-UNLIM   | -40 to 85    | MP222EI                 | <a href="#">Samples</a> |
| MAX3222EIDBR     | ACTIVE        | SSOP         | DB                 | 20   | 2000           | RoHS & Green    | NIPDAU                               | Level-1-260C-UNLIM   | -40 to 85    | MP222EI                 | <a href="#">Samples</a> |
| MAX3222EIDW      | ACTIVE        | SOIC         | DW                 | 20   | 25             | RoHS & Green    | NIPDAU                               | Level-1-260C-UNLIM   | -40 to 85    | MAX3222EI               | <a href="#">Samples</a> |
| MAX3222EIDWR     | ACTIVE        | SOIC         | DW                 | 20   | 2000           | RoHS & Green    | NIPDAU                               | Level-1-260C-UNLIM   | -40 to 85    | MAX3222EI               | <a href="#">Samples</a> |
| MAX3222EIPW      | ACTIVE        | TSSOP        | PW                 | 20   | 70             | RoHS & Green    | NIPDAU                               | Level-1-260C-UNLIM   | -40 to 85    | MP222EI                 | <a href="#">Samples</a> |
| MAX3222EIPWG4    | ACTIVE        | TSSOP        | PW                 | 20   | 70             | RoHS & Green    | NIPDAU                               | Level-1-260C-UNLIM   | -40 to 85    | MP222EI                 | <a href="#">Samples</a> |
| MAX3222EIPWR     | ACTIVE        | TSSOP        | PW                 | 20   | 2000           | RoHS & Green    | NIPDAU                               | Level-1-260C-UNLIM   | -40 to 85    | MP222EI                 | <a href="#">Samples</a> |

(1) The marketing status values are defined as follows:

**ACTIVE:** Product device recommended for new designs.

**LIFEBUY:** TI has announced that the device will be discontinued, and a lifetime-buy period is in effect.

**NRND:** Not recommended for new designs. Device is in production to support existing customers, but TI does not recommend using this part in a new design.

**PREVIEW:** Device has been announced but is not in production. Samples may or may not be available.

**OBSELETE:** TI has discontinued the production of the device.

(2) **RoHS:** TI defines "RoHS" to mean semiconductor products that are compliant with the current EU RoHS requirements for all 10 RoHS substances, including the requirement that RoHS substance do not exceed 0.1% by weight in homogeneous materials. Where designed to be soldered at high temperatures, "RoHS" products are suitable for use in specified lead-free processes. TI may reference these types of products as "Pb-Free".

---

**RoHS Exempt:** TI defines "RoHS Exempt" to mean products that contain lead but are compliant with EU RoHS pursuant to a specific EU RoHS exemption.

**Green:** TI defines "Green" to mean the content of Chlorine (Cl) and Bromine (Br) based flame retardants meet JS709B low halogen requirements of  $\leq 1000$ ppm threshold. Antimony trioxide based flame retardants must also meet the  $\leq 1000$ ppm threshold requirement.

<sup>(3)</sup> MSL, Peak Temp. - The Moisture Sensitivity Level rating according to the JEDEC industry standard classifications, and peak solder temperature.

<sup>(4)</sup> There may be additional marking, which relates to the logo, the lot trace code information, or the environmental category on the device.

<sup>(5)</sup> Multiple Device Markings will be inside parentheses. Only one Device Marking contained in parentheses and separated by a "~" will appear on a device. If a line is indented then it is a continuation of the previous line and the two combined represent the entire Device Marking for that device.

<sup>(6)</sup> Lead finish/Ball material - Orderable Devices may have multiple material finish options. Finish options are separated by a vertical ruled line. Lead finish/Ball material values may wrap to two lines if the finish value exceeds the maximum column width.

**Important Information and Disclaimer:** The information provided on this page represents TI's knowledge and belief as of the date that it is provided. TI bases its knowledge and belief on information provided by third parties, and makes no representation or warranty as to the accuracy of such information. Efforts are underway to better integrate information from third parties. TI has taken and continues to take reasonable steps to provide representative and accurate information but may not have conducted destructive testing or chemical analysis on incoming materials and chemicals. TI and TI suppliers consider certain information to be proprietary, and thus CAS numbers and other limited information may not be available for release.

In no event shall TI's liability arising out of such information exceed the total purchase price of the TI part(s) at issue in this document sold by TI to Customer on an annual basis.

**TAPE AND REEL INFORMATION**


\*All dimensions are nominal


| Device       | Package Type | Package Drawing | Pins | SPQ  | Reel Diameter (mm) | Reel Width W1 (mm) | A0 (mm) | B0 (mm) | K0 (mm) | P1 (mm) | W (mm) | Pin1 Quadrant |
|--------------|--------------|-----------------|------|------|--------------------|--------------------|---------|---------|---------|---------|--------|---------------|
| MAX3222ECDBR | SSOP         | DB              | 20   | 2000 | 330.0              | 16.4               | 8.2     | 7.5     | 2.5     | 12.0    | 16.0   | Q1            |
| MAX3222ECDWR | SOIC         | DW              | 20   | 2000 | 330.0              | 24.4               | 10.8    | 13.3    | 2.7     | 12.0    | 24.0   | Q1            |
| MAX3222ECPWR | TSSOP        | PW              | 20   | 2000 | 330.0              | 16.4               | 6.95    | 7.0     | 1.4     | 8.0     | 16.0   | Q1            |
| MAX3222EIDBR | SSOP         | DB              | 20   | 2000 | 330.0              | 16.4               | 8.2     | 7.5     | 2.5     | 12.0    | 16.0   | Q1            |
| MAX3222EIDWR | SOIC         | DW              | 20   | 2000 | 330.0              | 24.4               | 10.8    | 13.3    | 2.7     | 12.0    | 24.0   | Q1            |
| MAX3222EIPWR | TSSOP        | PW              | 20   | 2000 | 330.0              | 16.4               | 6.95    | 7.0     | 1.4     | 8.0     | 16.0   | Q1            |

## TAPE AND REEL BOX DIMENSIONS



\*All dimensions are nominal

| Device       | Package Type | Package Drawing | Pins | SPQ  | Length (mm) | Width (mm) | Height (mm) |
|--------------|--------------|-----------------|------|------|-------------|------------|-------------|
| MAX3222ECDBR | SSOP         | DB              | 20   | 2000 | 853.0       | 449.0      | 35.0        |
| MAX3222ECDWR | SOIC         | DW              | 20   | 2000 | 367.0       | 367.0      | 45.0        |
| MAX3222ECPWR | TSSOP        | PW              | 20   | 2000 | 853.0       | 449.0      | 35.0        |
| MAX3222EIDBR | SSOP         | DB              | 20   | 2000 | 853.0       | 449.0      | 35.0        |
| MAX3222EIDWR | SOIC         | DW              | 20   | 2000 | 367.0       | 367.0      | 45.0        |
| MAX3222EIPWR | TSSOP        | PW              | 20   | 2000 | 853.0       | 449.0      | 35.0        |



## NOTES:

1. All linear dimensions are in millimeters. Dimensions in parenthesis are for reference only. Dimensioning and tolerancing per ASME Y14.5M.
2. This drawing is subject to change without notice.
3. This dimension does not include mold flash, protrusions, or gate burrs. Mold flash, protrusions, or gate burrs shall not exceed 0.15 mm per side.
4. This dimension does not include interlead flash. Interlead flash shall not exceed 0.43 mm per side.
5. Reference JEDEC registration MS-013.

**DW0020A**

### SOIC - 2.65 mm max height

SOIC



LAND PATTERN EXAMPLE  
SCALE:6X



## SOLDER MASK DETAILS

4220724/A 05/2016

NOTES: (continued)


6. Publication IPC-7351 may have alternate designs.  
7. Solder mask tolerances between and around signal pads can vary based on board fabrication site.

## EXAMPLE STENCIL DESIGN

DW0020A

SOIC - 2.65 mm max height

SOIC



SOLDER PASTE EXAMPLE  
BASED ON 0.125 mm THICK STENCIL  
SCALE:6X

4220724/A 05/2016

NOTES: (continued)


8. Laser cutting apertures with trapezoidal walls and rounded corners may offer better paste release. IPC-7525 may have alternate design recommendations.
9. Board assembly site may have different recommendations for stencil design.





## SSOP - 2 mm max height

## SMALL OUTLINE PACKAGE



4214851/B 08/2019

1. All linear dimensions are in millimeters. Any dimensions in parenthesis are for reference only. Dimensioning and tolerancing per ASME Y14.5M.
2. This drawing is subject to change without notice.
3. This dimension does not include mold flash, protrusions, or gate burrs. Mold flash, protrusions, or gate burrs shall not exceed 0.15 mm per side.
4. This dimension does not include interlead flash. Interlead flash shall not exceed 0.25 mm per side.
5. Reference JEDEC registration MO-150.

# EXAMPLE BOARD LAYOUT

DB0020A

SSOP - 2 mm max height

SMALL OUTLINE PACKAGE



LAND PATTERN EXAMPLE  
EXPOSED METAL SHOWN  
SCALE: 10X



SOLDER MASK DETAILS

4214851/B 08/2019

NOTES: (continued)

6. Publication IPC-7351 may have alternate designs.

7. Solder mask tolerances between and around signal pads can vary based on board fabrication site.

## EXAMPLE STENCIL DESIGN

DB0020A

SSOP - 2 mm max height

SMALL OUTLINE PACKAGE



SOLDER PASTE EXAMPLE  
BASED ON 0.125 mm THICK STENCIL  
SCALE: 10X

4214851/B 08/2019

NOTES: (continued)

8. Laser cutting apertures with trapezoidal walls and rounded corners may offer better paste release. IPC-7525 may have alternate design recommendations.
9. Board assembly site may have different recommendations for stencil design.

PW (R-PDSO-G20)

PLASTIC SMALL OUTLINE



- NOTES:
- A. All linear dimensions are in millimeters. Dimensioning and tolerancing per ASME Y14.5M-1994.
  - B. This drawing is subject to change without notice.
  - C. Body length does not include mold flash, protrusions, or gate burrs. Mold flash, protrusions, or gate burrs shall not exceed 0,15 each side.
  - D. Body width does not include interlead flash. Interlead flash shall not exceed 0,25 each side.
  - E. Falls within JEDEC MO-153

PW (R-PDSO-G20)

PLASTIC SMALL OUTLINE



- NOTES:
- A. All linear dimensions are in millimeters.
  - B. This drawing is subject to change without notice.
  - C. Publication IPC-7351 is recommended for alternate design.
  - D. Laser cutting apertures with trapezoidal walls and also rounding corners will offer better paste release. Customers should contact their board assembly site for stencil design recommendations. Refer to IPC-7525 for other stencil recommendations.
  - E. Customers should contact their board fabrication site for solder mask tolerances between and around signal pads.

## IMPORTANT NOTICE AND DISCLAIMER

TI PROVIDES TECHNICAL AND RELIABILITY DATA (INCLUDING DATASHEETS), DESIGN RESOURCES (INCLUDING REFERENCE DESIGNS), APPLICATION OR OTHER DESIGN ADVICE, WEB TOOLS, SAFETY INFORMATION, AND OTHER RESOURCES "AS IS" AND WITH ALL FAULTS, AND DISCLAIMS ALL WARRANTIES, EXPRESS AND IMPLIED, INCLUDING WITHOUT LIMITATION ANY IMPLIED WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE OR NON-INFRINGEMENT OF THIRD PARTY INTELLECTUAL PROPERTY RIGHTS.

These resources are intended for skilled developers designing with TI products. You are solely responsible for (1) selecting the appropriate TI products for your application, (2) designing, validating and testing your application, and (3) ensuring your application meets applicable standards, and any other safety, security, or other requirements. These resources are subject to change without notice. TI grants you permission to use these resources only for development of an application that uses the TI products described in the resource. Other reproduction and display of these resources is prohibited. No license is granted to any other TI intellectual property right or to any third party intellectual property right. TI disclaims responsibility for, and you will fully indemnify TI and its representatives against, any claims, damages, costs, losses, and liabilities arising out of your use of these resources.

TI's products are provided subject to TI's Terms of Sale ([www.ti.com/legal/termsofsale.html](http://www.ti.com/legal/termsofsale.html)) or other applicable terms available either on [ti.com](http://ti.com) or provided in conjunction with such TI products. TI's provision of these resources does not expand or otherwise alter TI's applicable warranties or warranty disclaimers for TI products.

Mailing Address: Texas Instruments, Post Office Box 655303, Dallas, Texas 75265  
Copyright © 2020, Texas Instruments Incorporated